



2- door underbench safety cabinet for bases and flammables

COMPLIANCE

ADVANTAGES

- INRS recommendations compliant
- Designed to be placed under-bench
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Especially designed to settle under the bench
- Equipment allowing space saving
- INRS recommendations compliant
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Doors with key locking system
- Possibility to add swivel castors, for an easy movement of the cabinet



TECHNICAL FEATURES

Model	BS60	Shipping dimensions HxWxD (mm)	870 x 1200 x 800
Cabinet materials	15/10th epoxy painted steel structure	Ventilation	Both inlet and outlet
Doors color	white RAL 9010 & yellow RAL 1024	Openings diameter (mm)	50
Number of doors	2	Number of compartments	2
Doors type	swing doors	Containment sump	60.00
Hinges	left	HS Code	94032080
Door closure	self-closing		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Filtration box built in PVC with activated carbon filter for organic and corrosive vapors (Réf : CDF-P)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

- 4 swivel castors 2 with locking (Réf : 4ROU)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
BS60	670 x 1100 x 500	(2x) 650 x 530 x 470	60		2	50	60.00